

AXIS W702 Docking Station 1-bay

AXIS W702 Docking Station 1-bay enables easy handling of the body worn cameras with fast charging, quick, secure and easy data offloading.

- > **Grab and go, ready when you are**
- > **Dock and go, for automatic reliable offloading and fast charging**
- > **Reliable docking connectors**
- > **Splash proof**



AXIS W702 Docking Station 1-bay

Network		Storage conditions
Network protocols	IPv4, IPv6 USGv6, HTTPS, Bonjour, DNS, NTP, TCP, UDP, ICMP, DHCP, ARP	-40 °C to 65 °C (-40 °F to 149 °F) Humidity 10-85% RH (non-condensing)
Throughput	100 Mbit/s	Approvals
General		EMC EN 55032 Class B, EN 55035, EN 61000-6-1, EN 61000-6-2, FCC Part 15 Subpart B Class B, ICES-3(B)/NMB-3(B), RCM AS/NZS CISPR 32 Class B
Capacity	1 bay	Safety IEC/EN/UL 62368-1
Casing	Plastic casing Color: black NCS S 9000-N	Environment IEC 60068-2-1, IEC 60068-2-14, IEC 60068-2-2, IEC 60068-2-78
Sustainability	PVC free	Network Compatible with NIST SP500-267 throughput
Power	4.8-5.2 V DC, max 9 W	Dimensions
Connectors	Shielded RJ45 10BASE-T/100BASE-TX DC input Pogo pin pads	Height: 47 mm (1.9 in) Width: 76 mm (3.0 in) Depth: 95 mm (3.8 in)
Operating conditions	0 °C to 40 °C (32 °F to 104 °F) Humidity 10-85% RH (non-condensing)	Weight
		125 g (0.28 lb)
		Warranty
		3-year warranty, see axis.com/warranty