

AXIS Q1951-E Thermal Camera

Optimal image contrast for video analytics

AXIS Q1951-E delivers a high-quality thermal video stream for reliable detection 24/7. Ideal for perimeter security, it includes AXIS Motion Guard, AXIS Fence Guard, and AXIS Loitering Guard for proactive surveillance. With a powerful analytics platform, it's easy to add third-party analytics. Built-in cybersecurity features prevent unauthorized access and safeguard your system. For instance, Axis Edge Vault protects your Axis device ID and simplifies authorization of Axis products on your network. AXIS Q1951-E also includes a Trusted Platform Module (TPM) that is FIPS 140-2 level 2 certified. Furthermore, this halogen-free, compact camera is robust and suitable even for harsh conditions.

- > **Reliable detection 24/7**
- > **Built-in cybersecurity features**
- > **Compact, robust, halogen-free design**
- > **Support for AI-based analytics**
- > **Electronic image stabilization (EIS)**



AXIS Q1951-E Thermal Camera

Models	AXIS Q1951-E 7 mm/13 mm/19 mm/35 mm		Built-in installation aids	Pixel counter
Camera				
Image sensor	Uncooled microbolometer 384x288 pixels, pixel size: 17 µm. Spectral range: 8–14 µm		Analytics	
Lens	Athermalized 7 mm Horizontal field of view: 55°, F1.18 Near focus distance: 1.3 m (4.3 ft) 13 mm Horizontal field of view: 28°, F1.0 Near focus distance: 4 m (13 ft) 19 mm Horizontal field of view: 19.4°, F1.23 Near focus distance: 8.5 m (28 ft) 35 mm Horizontal field of view: 10.5°, F1.14 Near focus distance: 33 m (108 ft)		Applications	
Sensitivity	NETD 40 mK @25C, F1.0		Included AXIS Motion Guard, AXIS Fence Guard, AXIS Loitering Guard AXIS Video Motion Detection, active tampering alarm, audio detection Supported AXIS Perimeter Defender with AI-based functionality Support for AXIS Camera Application Platform enabling installation of third-party applications, see axis.com/acap	
System on chip (SoC)				
Model	ARTPEC-7		Approvals	
Memory	1024 MB RAM, 512 MB Flash		EMC	
Video				
Video compression	H.264 (MPEG-4 Part 10/AVC) Baseline, Main, and High Profiles H.265 (MPEG-H Part 2/HEVC) Main Profile Motion JPEG		CISPR 24, CISPR 35, EN 50121-4, EN 55024, EN 55032 Class A, EN 55035, EN 61000-6-1, EN 61000-6-2, IEC 62236-4 Australia/New Zealand: RCM AS/NZS CISPR32 Class A Canada: ICES-3(A)/NMB-3(A) Japan: VCCI Class A Korea: KC KN32 Class A, KC KN35 USA: FCC Part 15 Subpart B Class A	
Resolution	Sensor is 384x288. Image can be scaled up to 768x576.		Safety	
Frame rate	Up to 8.3 fps and 30 fps		IEC/EN/UL 60950-22, IEC/EN/UL 62368-1, IS 13252	
Video streaming	Multiple, individually configurable streams in H.264, H.265, and Motion JPEG Axis Zipstream technology in H.264 and H.265 Controllable frame rate and bandwidth VBR/ABR/MBR H.264/H.265 Video streaming indicator		Environment	
Image settings	Contrast, brightness, sharpness, exposure zones, compression, rotation: auto, 0°, 90°, 180°, 270° including Corridor Format, mirroring, dynamic text and image overlay, polygon privacy mask, electronic image stabilization		IEC 60068-2-1, IEC/EN 60068-2-14, IEC 60068-2-2, IEC 60068-2-27, IEC 60068-2-6, IEC/EN 60068-2-78, IEC/EN 60529 IP66/IP67, IEC/EN 62262 IK10 ^a , ISO 21207 Method B, MIL-STD-810H (Method 501.7, 502.7, 505.7, 506.6, 507.6, 509.7, 510.7, 514.8, 516.8, 521.4), NEMA 250 Type 4X, NEMA TS 2 (2.2.7-2.2.9)	
Audio				
Audio streaming	Audio in, simplex, two-way audio via edge-to-edge technology		Network	
Audio encoding	24bit LPCM, AAC-LC 8/16/32/48 kHz, G.711 PCM 8 kHz, G.726 ADPCM 8 kHz, Opus 8/16/48 kHz Configurable bit rate		NIST SP500-267	
Audio input/output	External microphone input or line input, digital audio input, network speaker pairing		Cybersecurity	
Network				
Network protocols	IPv4, IPv6 USGv6, ICMPv4/ICMPv6, HTTP, HTTPS, HTTP/2, TLS, QoS Layer 3 DiffServ, FTP, SFTP, CIFS/SMB, SMTP, Bonjour, UPnP®, SNMP v1/v2c/v3 (MIB-II), DNS/DNSv6, DDNS, NTP, NTS, RTSP, RTP, SRTP/RTSPS, TCP, UDP, IGMPv1/v2/v3, RTCP, DHCPv4/v6, SSH, LLDP, CDP, MQTT v3.1.1, Secure syslog (RFC 3164/5424, UDP/TCP/TLS), Link-Local address (ZeroConf)		ETSI EN 303 645	
System integration				
Application Programming Interface	Open API for software integration, including VAPIX® and AXIS Camera Application Platform; specifications at axis.com One-click cloud connection ONVIF® Profile G, ONVIF® Profile M, ONVIF® Profile S, and ONVIF® Profile T, specification at onvif.org		Cybersecurity	
Onscreen controls	Heater, electronic image stabilization		Edge security	
Event conditions	Analytics, operating temperature, supervised external input, edge storage events, digital audio, virtual inputs through API		Software: Signed firmware, brute force delay protection, digest authentication and OAuth 2.0 RFC6749 OpenID Authorization Code Flow for centralized ADFS account management, password protection, AES-XTS-Plain64 256bit SD card encryption Hardware: Axis Edge Vault cybersecurity platform TPM 2.0 (CC EAL4+, FIPS 140-2 Level 2), secure element (CC EAL 6+), Axis device ID, secure keystore, signed video, secure boot	
Event actions	Record video: SD card and network share Upload of images or video clips: FTP, SFTP, HTTP, HTTPS, network share and email Pre- and post-alarm video or image buffering for recording or upload Notification: email, HTTP, HTTPS, TCP and SNMP trap Overlay text, play audio clip, I/O, MQTT		Network security	
Data streaming	Event data		IEEE 802.1X (EAP-TLS, PEAP-MSCHAPv2), IEEE 802.1AE (MACsec PSK/EAP-TLS), IEEE 802.1AR, HTTPS/HSTS, TLS v1.2/v1.3, Network Time Security (NTS), X.509 Certificate PKI, host-based firewall	
Documentation				
AXIS OS Hardening Guide Axis Vulnerability Management Policy Axis Security Development Model AXIS OS Software Bill of Material (SBOM) To download documents, go to axis.com/support/cybersecurity/resources To read more about Axis cybersecurity support, go to axis.com/cybersecurity				
General				
Casing	IP66/IP67-, NEMA 4X-, and IK10-rated ^a casing Polycarbonate blend, aluminum and a germanium window Color: white NCS S 1002-B		Casing	
Sustainability	PVC free, BFR/CFR free		IP66/IP67-, NEMA 4X-, and IK10-rated ^a casing Polycarbonate blend, aluminum and a germanium window Color: white NCS S 1002-B	
Power	Power over Ethernet (PoE) IEEE 802.3af/802.3at Type 1 Class 3 Typical 4.96 W, max 12.95 W 12-28 V DC, typical 4.92 W, max 12.95 W		Sustainability	
Connectors	Shielded RJ45 10BASE-T/100BASE-TX/1000BASE-T 3.5 mm mic/line in Terminal block for 1 supervised alarm input and 1 output (12 V DC output, max. load 25 mA) DC input, terminal block		PVC free, BFR/CFR free	
Storage	Support for microSD/microSDHC/microSDXC card Support for SD card encryption (AES-XTS-Plain64 256bit) Recording to network-attached storage (NAS) For SD card and NAS recommendations see axis.com		Power	
Operating conditions	-40 °C to 60 °C (-40 °F to 140 °F) Maximum temperature according to NEMA TS 2 (2.2.7): 74 °C (165 °F) Humidity 10-100% RH (condensing) De-icing capability, compliant to MIL-STD-810H Method 521.4		Connectors	

Storage conditions	-40 °C to 65 °C (-40 °F to 149 °F) Humidity 5-95% RH (non-condensing)
Dimensions	Ø132 x 272 mm (Ø5.2 x 10.7 in)
Weight	1400 g (3.1 lb)
Included accessories	Installation guide, Windows® decoder 1-user license, Resistorx® L-key, wall and ceiling mount bracket, terminal block connectors, connector guard
Optional accessories	AXIS T94F01M J-Box/Gang Box Plate, AXIS T91A47 Pole Mount, AXIS T94P01B Corner Bracket, AXIS T94F01P Conduit Back Box, AXIS Weather Shield K, Axis PoE Midspans For more accessories, see axis.com

Video management software	AXIS Companion, AXIS Camera Station, video management software from Axis Application Development Partners available at axis.com/vms
Languages	English, German, French, Spanish, Italian, Russian, Simplified Chinese, Japanese, Korean, Portuguese, Polish, Traditional Chinese, Dutch, Czech, Swedish, Finnish, Turkish, Thai, Vietnamese
Warranty	5-year warranty, see axis.com/warranty
Export control	This product is subject to export control regulations, and you should always comply with all applicable national and international export or re-export control regulations.

a. Excluding front window