

0

DS-PWA96-Kit-WB/12V

- · DS-PWA96-M-WB/12V x 1
- DS-PKF1-WB x 1
- · DS-PDP15P-EG2-WB x 1
- · DS-PDMC-EG2-WB x 1





Specification

Tag48Area32Cones95 (up to 48 PIRCAMs)Onboard video clips4Instaler1User46Admin1Vice PromptSupportedLoudspeaker built inSupportedTag reader built inSupportedAdmony to store5000Programming toolsHik-Connect/Hik-ProConnect/Web Portal / IVMS4200/ Convergence CloudFirmware uggradeAPP/Web PortalAutomatic Am/Disarm TimersSupportedSupportedSupportedAutomatic Am/Disarm TimersSupportedSupportedSupportedDiagnostics via the APP or WebSupportedSupportedSupportedSupportedSupportedSupportedSupportedSupportedSupportedSupportedSupportedSupportedSupportedWeb server for maintenance (offline configuration)SupportedSupportedSupportedHardware EdeteSupportedSta ZOOS(Si I keel 2, Contact 1D), ISUP, ISAPI (SDK)Hardware EdeteSupportedReserver for maintenance (offline configuration)SupportedSupportedSupportedSupportedSupportedSta ZOOS(Si I keel 2, Contact 1D), ISUP, ISAPI (SDK)Hardware EdeteSupportedSupportedSupportedSupportedSupportedSupportedSupportedSupportedSupportedSupportedSupportedSupported <th>Software features</th> <th></th>	Software features				
Zones96 (up to 48 PIRCAMS)Onboard video clips4Installer1User46Admin1Voice PromptSupportedLoudspeaker built inSupportedMemory Log stored500Programming toolsHik-Connect/Hik-ProConnect/Web Portal/ IVMS4200/ Convergence CloudFirmware upgradeAPP/Web PortalArm modesAway/StayAutomatic Arm/Disarm TimersSupportedSupportedSupportedForced Arming with Open ZonesSupportedProgramming toolsHik-Procencet IVIN, ISUP, ISAPI (SDK)ARC protocolSIA DCO9(SIA level 2, Contact ID), ISUP, ISAPI (SDK)Hik-IP Receiver & Hik-IP Receiver Pro (Sur-Gard & Ademco 685) SupportedSupportedSupportedWeb server for maintenance (offine configuration)SupportedHarder FeaturesSupportedSta ZoutputSupportedSta ZoutputSupportedSta ZoutputSupportedSta SoutputSupportedSta SoutputSupportedWeb server for maintenance (offine configuration)SupportedHarder FeaturesTTwo-way WirelessSupportedCommunicationSupportedR Frequency433MhzArtenansisionSupportedSupportedSupportedSupportedSupportedSupportedSupportedSupportedSupportedSupportedSupportedSupportedSupportedSupported<	Тад	48			
Onboard video clips4Installer1User46Admin1Voice PromptSupportedLoudspeaker built inSupportedTag reader built inSupportedMemory Log stored5000Programming toolsHik-Connect/Hik-ProConnect/Web Portal/ IVMS4200/ Convergence CloudFirmware uggradeAPP/Web PortalArm modesMawy/StayAutomatic Arm/Disarm TimersSupportedDiagnostics via the APP or WebSupportedSiA DCO9(SIA level 2, Contact ID), ISUP, ISAPI (SDK)Hik-IP Receiver A Hik-IP Receiver Pro (Sur-Gard & Ademco 685) SupportedUser APP for operatingSupportedUser APP for porgrammingSupportedInstaller APP for programmingSupportedInstaller A	Area	32			
Installer1User46Admin1Voice PromptSupportedLoudspeaker built inSupportedTag reader built inSupportedMemory Log stored5000Programming toolsHik-Connect/Hik-ProConnect/Web Portal/ IVMS4200/ Convergence CloudFirmware ungradeAPP/Web PortalArm modesAway/StayAutomatic Arm/Disar TimersSupportedJoing out to APP or WebSupportedJoing out to APP or WebSupportedSuppo	Zones	96 (up to 48 PIRCAMs)			
User46Admin1Voice PromptSupportedLoudspeaker built inSupportedMemory Log stored5000Programming toolsHik-Connect/Hik-ProConnect/Web Portal/ IVMS4200/ Convergence CloudFirmware upgradeAPP/Web PortalArm modesAway/SayAutomatic Arm/Disarm TimersSupportedForced Arming with Open ZonesSupportedPorger Arming with Open ZonesSupportedPorced Arming with Open ZonesSupportedARC protocolHik-LP Receiver & Hik-IP Receiver Pro (Sur-Gard & Ademco 685) Supports video verification and remote controlUser APP for operatingSupportedUses APP for operatingSupportedSupportedSupportedHik-IP Receiver & Hik-IP Receiver Pro (Sur-Gard & Ademco 685) Supports video verification and remote controlUses APP for operatingSupportedInstaller APP for programmingSupportedBordedSupportedForeuresSupportedForeuresSupportedFrasmissionSupportedFrasmissionSupportFrequency Hoping 128 AES EncryptionVireless SecuritySupportedSupportedSupportedSupportedSupportedPower supplySupportedPower supplySupported	Onboard video clips	4			
Admin1Voice PromptSupportedLoudspeaker built inSupportedTag reader built inSupportedMemory Log storedS000Programming toolsHik-Connect/Hik-ProConnect/Web Portal/ IVMS4200/ Convergence CloudFirmware upgradeAPP/Web PortalArm modesAway/StayAutomatic Arm/Disar TimersSupportedForced Arming with Open ZonesSupportedJagnostics via the APP or WebSupportedJagnostics via the APP or WebSupportedARC protocolHik-IP Receiver & Hik-IP Receiver Pro (Sur-Gard & Ademco 685) Supports video verification and remote controlUser APP for programming SupportedSupportedWeb server for maintenance (offline configuration)SupportedHardware featuresSupportedRS22 outputSupportedRT aromsisionSupportRF requency433MtzRF requencyAgaMtzArgencySupportedVireless SecuritySupportedVireless SecuritySupportedVireless SecuritySupportedSylandSupported	Installer	1			
Voice PromptSupportedLoudspeaker built inSupportedTag reader built inSupportedMemory Log stored5000Programming toolsHik-Connect/Hik-ProConnect/Web Portal/ IVMS4200/ Convergence CloudFirmware upgradeAPP/Web PortalAutomatic Arm/Disarm TimersSupportedForced Arming with Open ZonesSupportedDiagnostics via the APP or WebSupportedARC protocolHik-P Receiver & Hik-IP Receiver Pro (Sur-Gard & Ademco 685) Supports video verification and remote controlUser APP for operatingSupportedNether StaffSupportedHik-IP Receiver & Hik-IP Receiver Pro (Sur-Gard & Ademco 685) Supports video verification and remote controlUser APP for operatingSupportedNether StaffSupportedHardwar featuresSupportedRS23 outputSupportedRT armstisionSupportedTwo-way Wireless CommunicationSupportRF requency433MlzArrigen StaffSupported <td>User</td> <td colspan="2">46</td>	User	46			
Loudspeaker built inSupportedTag reader built inSupportedMemory Log stored5000Programming toolsHik-Connect/Hik-ProConnect/Web Portal/ IVM54200/ Convergence CloudFirmware upgradeAPP/Web PortalArm modesAway/StayAutomatic Arm/Disarm TimersSupportedForced Arming with Open ZonesSupportedForced Arming with Open ZonesSupportedAutomatic Arm/Disarm TimersSupportedSupportedSupportedProgrammingSupportedARC protocolSupportedInstaller APP for operatingSupportedSupportedSupportedInstaller APP for operatingSupportedRS222 outputSupportedSusportedSupportedInstaller APP for operatingSupportedRS222 outputSupportedSusportedSupportedInstaller APP for operatingSupportedSupportedSupportedInstaller APP for operatingSupportedSupportedSupportedInstaller APP for operatingSupportedSupportedSupportedInstaller APP for operatingSupportedSuppor	Admin	1			
Tag reader built inSupportedMemory Log stored5000Programming toolsHik-Connect/Hik-ProConnect/Web Portal/IVMS4200/ Convergence CloudFirmware upgradeAPP/Web PortalArm modesAway/StayAutomatic Arm/Disarm TimersSupportedForced Arming with Open ZonesSupportedDiagnostics via the APP or WebSupportedARC protocolSiA DCO9(SIA level 2, Contact ID), ISUP, ISAPI (SDK)Hik-IP Receiver & Hik-IP Receiver Pro (Sur-Gard & Ademco 685) SupportedUser APP for operatingSupportedInstaller APP for programmingSupportedWeb server for maintenance (offline configuration)SupportedRS232 outputSupportedSupportSupportedSupportedSupportedInstaller APP for programmingSupportedWeb server for maintenance (offline configuration)SupportedRS232 outputSupportedSupportedSupportedInstaller APP for programmingSupportedWireless CommunicationSupportedIf requency433MtzAt requencyA33MtzAt requencySupportedSuportedSupported <td>Voice Prompt</td> <td colspan="2">Supported</td>	Voice Prompt	Supported			
Nemory Log stored5000Programming toolsHik-Connect/Hik-ProConnect/Web Portal/ IVMS4200/ Convergence CloudFirmware upgradeAPP/Web PortalArm modesAway/StayAutomatic Arm/Disarm TimersSupportedForced Arming with Open ZonesSupportedDiagnostics via the APP or WebSupportedARC protocolHik-IP Receiver & Hik-IP Receiver Pro (Sur-Gard & Ademco 685) Supports video verification and remote controlUser APP for operatingSupportedInstaller APP for programmingSupportedGoffine configuration)SupportedHardware featuresSupportedRS232 outputSupportedSIM SlotDualRF frequency433MhzRF FrequencyA33MbzKireless SecurityFrequency Hoping 128 AES EncryptionStdG on boardSupportedPower supplyBuilt in power supply	Loudspeaker built in	Supported			
Programming toolsHik-Connect/Hik-ProConnect/Web Portal/ IVMS4200/ Convergence CloudFirmware upgradeAPP/Web PortalArm modesAway/StayAutomatic Arm/Disarm TimersSupportedForced Arming with Open ZonesSupportedDiagnostics via the APP or WebSupportedARC protocolHik-IP Receiver & Lik-IP Receiver Pro (Sur-Gard & Ademco 685) Supports video verification and remote controlUser APP for operatingSupportedInstaller APP for porgrammingSupportedGoffline configuration)SupportedHardware featuresSupportedRS232 outputSupportedSIM slotDualRF frequencyA33MhzRF frequencyA33MhzVireless SecuritySupportedSylac DougSupportedSylac DougSupportedSupportSupported	Tag reader built in	Supported			
Firmware upgradeAPP/Web PortalArm modesAway/StayAutomatic Arm/Disarm TimersSupportedForced Arming with Open ZonesSupportedDiagnostics via the APP or WebSupportedARC protocolSiA DCO9(SIA level 2, Contact ID), ISUP, ISAPI (SDK)Hik-IP Receiver & Hik-IP Receiver Pro (Sur-Gard & Ademco 685) Supports video verification and remote controlUser APP for operatingSupportedInstaller APP for programmingSupportedWeb server for maintenance (offline configuration)SupportedHardware featuresSupportedRS23 outputSupportedSIM slotDualPrensmissionSupportTwo-way Wireless CommunicationSupportedRF Frequency433MhzWireless SecuritySupported3/4G on boardSupportedPower supplyBuilt in power supply	Memory Log stored	5000			
Arm modesAway/StayAutomatic Arm/Disarm TimersSupportedForced Arming with Open ZonesSupportedDiagnostics via the APP or WebSupportedARC protocolSIA DCO9(SIA level 2, Contact ID), ISUP, ISAPI (SDK)Hik-IP Receiver & Hik-IP Receiver Pro (Sur-Gard & Ademco 685) Supports video verification and remote controlUser APP for operatingSupportedWeb server for maintenance (offline configuration)SupportedHardware featuresSupportedRS232 outputSupportedSIM slotDualRF transmissionSupportTwo-way Wireless CommunicationSupportRF Frequency433MhzKireless SecuritySuportedSupportedSupportedSupportSupportedYireless SecuritySupportedSupportSupportedSupportSupportedPower supplyBuilt in power supply	Programming tools	Hik-Connect/Hik-ProConnect/Web Portal/ IVMS4200/ Convergence Cloud			
Automatic Arm/Disarm TimersSupportedForced Arming with Open ZonesSupportedDiagnostics via the APP or WebSupportedARC protocolSIA DCO9(SIA level 2, Contact ID), ISUP, ISAPI (SDK)ARC protocolHik-IP Receiver & Hik-IP Receiver Pro (Sur-Gard & Ademco 685) Supports video verification and remote controlUser APP for operatingSupportedInstaller APP for programmingSupportedWeb server for maintenance (offline configuration)SupportedRS232 outputSupportedSIM slotDualRF transmissionSupportTwo-way Wireless CommunicationSupportRF Frequency433MhzRF FrequencySupportedJ/AG on boardSuportedSuportedSupportedPower supplyBuilt in power supply	Firmware upgrade	APP/Web Portal			
Forced Arming with Open ZonesSupportedDiagnostics via the APP or WebSupportedARC protocolSIA DC09(SIA level 2, Contact ID), ISUP, ISAPI (SDK) Hik-IP Receiver & Hik-IP Receiver Pro (Sur-Gard & Ademco 685) Supports video verification and remote controlUser APP for operatingSupportedInstaller APP for programmingSupportedWeb server for maintenance (offline configuration)SupportedHardware featuresSupportedRS232 outputSupportedSilv SolutDualRF transmissionSupportTwo-way Wireless CommunicationSupportRF Frequency433MhzVireless SecuritySupportedSilver ApportedSupportedJAG on boardSupportedFectrical characteristicsSupportedPower supplyBuilt in power supply	Arm modes	Away/Stay			
Diagnostics via the APP or WebSupportedARC protocolSIA DC09(SIA level 2, Contact ID), ISUP, ISAPI (SDK) Hik-IP Receiver & Hik-IP Receiver Pro (Sur-Gard & Ademco 685) Supports video verification and remote controlUser APP for operatingSupportedInstaller APP for programmingSupportedWeb server for maintenance (offline configuration)SupportedHardware featuresSupportedRS232 outputSupportedSilve SolutputDualRF transmissionSupportTwo-way Wireless CommunicationSupportArgency433MhzVireless SecuritySupportedSilve SolutputSupportedSupportedSupportedSupportS	Automatic Arm/Disarm Timers	Supported			
ARC protocolSIA DC09(SIA level 2, Contact ID), ISUP, ISAPI (SDK) Hik-IP Receiver & Hik-IP Receiver Pro (Sur-Gard & Ademco 685) Supports video verification and remote controlUser APP for operatingSupportedInstaller APP for programmingSupportedWeb server for maintenance (offline configuration)SupportedRS232 outputSupportedRS232 outputSupportedSiM slotDualRF transmissionJuportTwo-way Wireless CommunicationSupportRF Frequency433MhzRF prequencySupportedJive securitySupportedSiA Do andSupportedSupportedSupportedPrequencySupportedARF prequencySupported	Forced Arming with Open Zones	Supported			
ARC protocolHik-IP Receiver & Hik-IP Receiver Pro (Sur-Gard & Ademco 685) Suports video verification and remote controlUser APP for operatingSuportedInstaller APP for programmingSuportedWeb server for maintenance (offline configuration)SuportedRs232 outputSuportedRs232 outputSuportedSilv SoloDualR f transmissionSuportTwo-way Wireless CommunicationSuportRs F Frequency433MhzKireless SecurityFrequency Hoping 128 AES EncryptionSilv SoloSuportedJAGon boardSuportedHertrical characteristicsFower supplyPower supplyBull in power supply	Diagnostics via the APP or Web	Supported			
IndexSupports video verification and remote controlUser APP for operatingSupportedInstaller APP for programmingSupportedWeb server for maintenance (offline configuration)SupportedHardware featuresSupportedRS232 outputSupportedSiM slotDualRF transmissionSupportTwo-way Wireless CommunicationSupportRF Frequency433MhzKirless SecurityFrequency Hoping 128 AES EncryptionSi/A Gon boardSupportedElectrical characteristicsFower supplyPower supplyBuilt in power supply		SIA DC09(SIA level 2, Contact ID), ISUP, ISAPI (SDK)			
User APP for operatingSupportedInstaller APP for programmingSupportedWeb server for maintenance (offline configuration)SupportedHardware featuresSupportedRS232 outputSupportedSiM slotDualRF transmissionSupportTwo-way Wireless CommunicationSupportRF Frequency433MhzKirless SecurityFrequency Hoping 128 AES Encryption3/4G on boardSupportedElectrical characteristicsSupportedPower supplyBuilt in power supply	ARC protocol	Hik-IP Receiver & Hik-IP Receiver Pro (Sur-Gard & Ademco 685)			
Installer APP for programmingSupportedWeb server for maintenance (offline configuration)supportedHardware featuressupportedRS232 outputSupportedSIM slotDualRF transmissionsupportTwo-way Wireless CommunicationSupportRF Frequency433MhzWireless Securityprequency Hoping 128 AES Encryption3/4G on boardSupportedElectrical characteristicsSupportedPower supplyBuilt in power supply		Supports video verification and remote control			
Web server for maintenance (offline configuration)supportedHardware featuressupportedRS232 outputSupportedSIM slotDualRt ransmissionsupportTwo-way Wireless CommunicationBupportRF Frequency433MhzWireless SecurityFrequency Hoping 128 AES Encryption3/4G on boardSupportedElectrical characteristicsBuilt in power supplyPower supplyBuilt in power supply	User APP for operating	Supported			
SupportedHardware featuresR5232 outputSupportedSIM slotDualRF transmissionTwo-way Wireless CommunicationSupportRF Frequency433MhzKarper SecurityFrequency Hopping 128 AES EncryptionSuportedSupportedSuportedSupportedBirder SecuritySupported<	Installer APP for programming	Supported			
Hardware featuresRS232 outputSuportedSIM slotDualRF transmissionSupportTwo-way Wireless CommunicationBupportRF Frequency433MhzWireless SecurityFrequency Hoping 128 AES Encryption3/4G on boardSupportedElectrical characteristicsBuilt in power supply	Web server for maintenance	Supported			
RS232 outputSupportedSIM slotDualRF transmissionSupportTwo-way Wireless CommunicationSupportRF Frequency433MhzWireless SecurityFrequency Hoping 128 AES Encryption3/4G on boardSupportedElectrical characteristicsJuportedPower supplyBuilt in power supply	(offline configuration)	Supported			
SIM slotDualRF transmissionTwo-way Wireless CommunicationsupportRF Frequency433MhzWireless Securityrequency Hoping 128 AES Encryption3/4G on boardsupportedElectrical characteristicsPower supplyBuilt in power supply	Hardware features				
RF transmissionTwo-way Wireless CommunicationSupportRF Frequency433MhzWireless SecurityFrequency Hoping 128 AES Encryption3/4G on boardSupportedElectrical characteristicsPower supplyBuilt in power supply	RS232 output	Supported			
Two-way Wireless CommunicationSupportRF Frequency433MhzWireless SecurityFrequency Hoping 128 AES Encryption3/4G on boardSupportedSupportedElectrical characteristicsPower supplyBuilt in power supply	SIM slot	Dual			
SupportRF Frequency433MhzWireless SecurityFrequency Hoping 128 AES Encryption3/4G on boardSupportedElectrical characteristicsPower supplyBuilt in power supply	RF transmission				
CommunicationRF Frequency433MhzWireless SecurityFrequency Hoping 128 AES Encryption3/4G on boardSupportedElectrical characteristicsPower supplyBuilt in power supply		Support			
Wireless SecurityFrequency Hoping 128 AES Encryption3/4G on boardSupportedElectrical characteristicsSupportedPower supplyBuilt in power supply	Communication	Support			
3/4G on boardSupportedBeterrical characteristicsPower supplyBuilt in power supply	RF Frequency	433Mhz			
Electrical characteristics Power supply Built in power supply	Wireless Security	Frequency Hoping 128 AES Encryption			
Power supply Built in power supply	3/4G on board	Supported			
	Electrical characteristics				
Battery type Built in on board Battery Li	Power supply	Built in power supply			
	Battery type	Built in on board Battery Li			



Battery life span	12 hours				
Wireless transmission	Wireless transmission				
Wired network	Supported				
Wi-Fi Standard	Supported				
Display					
LEDs Status	Arm/Disarm, Alarm, Tamper, Fault, Cloud, Power				
General					
Operation temperature	-10 °C to +55 °C				
Shell material	Plastic				
Dimension(WxHxD)	170.0 mm (6.7") x 170.0 (6.7") mm x 38.6 mm (1.5")				
Weight	557.5 g(19.7 oz)				
Color	white				
Power supply	8~24 VDC wide range of power supply				
Device management					
Keyfob	48				
Wireless sounder	6				
Keypad	8 (Including Tag reader)				
Wireless Repeater	4				
PIR Cam	Supported				

Available Model

DS-PWA96-Kit-WB/12V

Accessory

Optional

DS-PDMC-EG2-WB Wireless Magnet Detector	DS-PDP15P-EG2-WB Wireless PIR Detector	DS-PKF1-WB Keyfob





Distributed by

Γ

L



Headquarters

No.555 Qianmo Road, Binjiang District, Hangzhou 310051, China T +86-571-8807-5998 overseasbusiness@hikvision.com

Hikvision USA T +1-909-895-0400 sales.usa@hikvision.com

Hikvision Australia T +61-2-8599-4233 salesau@hikvision.com

Hikvision India T +91-22-28469900 sales@pramahikvision.com

Hikvision Canada T +1-866-200-6690 sales.canada@hikvision.com

Hikvision Thailand T +662-275-9949 sales.thailand@hikvision.com Hikvision Europe T +31-23-5542770 sales.eu@hikvision.com

Hikvision Italy T +39-0438-6902 info.it@hikvision.com

Hikvision Brazil T +55 11 3318-0050 Latam.support@hikvision.com

Hikvision Turkey T +90 (216)521 7070- 7074 sales.tr@hikvision.com

Hikvision Malaysia T +601-7652-2413 sales.my@hikvision.com Hikvision UK & Ireland T +01628-902140 sales.uk@hikvision.com

Hikvision South Africa Tel: +27 (10) 0351172 sale.africa@hikvision.com

Hikvision France T +33(0)1-85-330-450 info.fr@hikvision.com

Hikvision Kazakhstan T +7-727-9730667 nikia.panfilov@hikvision.ru

Hikvision Vietnam T +84-974270888 sales.vt@hikvision.com Hikvision UAE T +971-4-4432090 salesme@hikvision.com

Hikvision Singapore T +65-6684-4718 sg@hikvision.com

Hikvision Spain T +34-91-737-16-55 info.es@hikvision.com

Hikvision Tashkent T +99-87-1238-9438 uzb@hikvision.ru

Hikvision Hong Kong T +852-2151-1761 info.hk@hikvision.com Hikvision Russia T +7-495-669-67-99 saleru@hikvision.com

Hikvision Korea T +82-(0)31-731-8817 sales.korea@hikvision.com

Hikvision Poland T +48-22-460-01-50 info.pl@hikvision.com

Hikvision Indonesia T +62-21-2933759 Sales.Indonesia@hikvision.com

Hikvision Colombia sales.colombia@hikvision.com

© Hikvision Digital Technology Co., Ltd. 2020 | Data subject to change without notice |