




OE-MD Gen. 3


Cloud-Managed Appliance

A cost-effective, IP recording solution, the OE-MD is available with a built-in 8 or 16 channel PoE switch.



INTEGRATED POE

Reduce costs and simplify installation with an integrated power-over-ethernet (PoE) switch.



DUAL GB NICS

Dual network ports allow use of an isolated camera network for security.



RACK MOUNTABLE

Mounting hardware included for convenient installation.



SSD OS DRIVE


Solid state OS drive provides improved reliability and fast boot times.

APPLIANCE SPECIFICATIONS


| | OE-MDX08 | OE-MDX16 |
|-----------------------------|---|---------------------------------------|
| Channel Count | 32 | |
| Recording Rate | 150Mbps | |
| Video Outputs | 1 x HDMI®, 1 x DisplayPort | |
| Video Signal Loss Detection | Yes | |
| Motion Detection | Server Side (Adjustable Sensitivity, Custom Grid) | |
| Native Analytics Support | Smart Motion Channels: 24 Limitation Apply. Click here to learn more. | |
| Remote Operation | Complete remote operation (Live view, Search, Setup, Updates) | |
| Remote Software | Web Client / Command Station Desktop Client / OpenEye Mobile Apps | |
| PTZ Control | IP Protocol | |
| Recording Mode | Continuous / Event / Continuous + Event | |
| Playback Search | Multi-channel playback / Calendar / Timeline / Thumbnail / Events | |
| Backup | Cloud / Network / USB | |
| USB Ports | Front: x2 USB 2.0 ports Rear: x2 USB 3.0 | |
| Digital Signature Support | AVI and JPG | |
| Operating System | Linux | |
| Storage Capacity (Size) | 16TB | Up to 40TB |
| Network | Dual GbE | |
| Power Supply | 180W | 200W |
| Power Rating | AC 100~240V, 2.5A, 50-60Hz | AC 100~240V, 3.5-2.5A, 50-60Hz |
| Max Power Consumption | Max: 125W Nominal: 30W | Max: 200W Nominal: 100W |
| Built-in PoE Ports | 8 | 16 |
| PoE Switch Loads | 100W | 120W |
| Max Operating Temperature | Max Operating Temperature: 104 °F (40 °C) | |
| Mounting Hardware | Wall Mount Brackets Included | Rack Mount Ears Included |
| Mouse | Included | |
| Country of Origin | Taiwan | |
| NDAA Compliant | Yes | |
| Dimensions | 8.7" x 1.7" x 10.8" (221 x 44 x 275mm) | 11.8" x 1.7" x 11" (300 x 44 x 280mm) |
| Unit Weight | 3.5lbs | 5lbs |
| Certification | UL / cUL / RMC / CE / FCC / Dictamen | |
| SSD OS Drive | Standard | |
| Storage Drives (Qty) | 1 | 2 |

DIMENSIONS


OE-MDX08 (Front)




OE-MDX08 (Back)



OE-MDX16 (Front)



OE-MDX16 (Back)



MODELS

OE-MDX08xx

8 Channel Recorder

OE-MDX16xx

16 Channel Recorder