

## DS-2FP2061 Indoor Security Microphone



- Support ceiling mounting, desktop mounting, and wall mounting
- Support centralized power supply, camera power supply, and DC power supply. Dedicated power supply is not required
- With high sensitivity and high fidelity, this microphone can pick up sounds which come from all directions, including a clear sound and high anti-disruption ability
- The built-in output driving circuit is able to directly drive earphones and other devices
- This device is suitable for pick up sounds within a close range. pickup range: up to 5 m, best pick up range: 3 m
- Support volume adjustment knob, which are used for adjusting volume according to surroundings.
- It is suitable for some practical situations like counter, cash register, meeting, negotiation, recording and so on
- There are built-in modules in the top of indoor pick-up, including power protection module, modules for protecting itself from lightning stroke and polarity reve
- Innovative circuit design, clear content and high fidelity sound



## Specification

| Microphone          |                                                   |
|---------------------|---------------------------------------------------|
| Туре                | electret                                          |
| Polar Pattern       | 360° omni-directional                             |
| Pickup Range        | 0 m to 5 m                                        |
| Frequency Response  | 20 Hz to 20 kHz                                   |
| Sensitivity         | -32 dB                                            |
| SNR                 | 90 dB                                             |
| Sampling Rate       | 8 khz, 16 khz(default), 32 khz                    |
| Dynamic Range       | 0 dB to 90 dB                                     |
| Function            |                                                   |
| LED Indicator       | Blue: Working normally                            |
| General             |                                                   |
| Power               | 12 VDC, max. 0.1 W                                |
| Material            | Plastic                                           |
| Weight              | Approx. 48 g (0.106 lb.)                          |
| Operating Condition | -10 °Cro 50 °C(14 °F to 122°F) (indoor)           |
| Dimension           | Ø85 mm × 20.48 mm (Ø3.35" × 0.81")                |
| Packing List        | Device × 1                                        |
|                     | Regulatory Compliance and Safety Information × 1  |
| Installation        | Ceiling mounting, wall mounting, desktop mounting |

## Available Model

DS-2FP2061



Headquarters No.555 Qianmo Road, Binjiang District, Hangzhou 310051, China T +86-571-8807-5998 www.hikvision.com

Follow us on social media to get the latest product and solution information.





HikvisionHQ



HikvisionHQ



Hikvision Corporate Channel



6 hikvisionhq