

HA-KIT-PY2

Two-wire Video Intercom Kit



- Indoor Station: 7" touch screen 2-Wire IP indoor station with 1024 × 600 resolution
- Indoor Station: Convenient Hik-Connect APP Mobile Control: receive calls, open the door and live view remotely
- Indoor Station: Easy wizard for quick set up
- Indoor Station: Live-view of the door station and cameras in public areas
- Indoor Station: Support voice messages when no response from the indoor station
- Door Station: High quality imaging with 2 MP resolution
- Door Station: One call physical button for easier calls
- Door Station: Two-lock control
- Door Station: IP65 protection level
- Door Station: Directly provide 12 V, 500 mA power output for one electronic lock without additional power supply
- Door Station: High-quality stainless steel panel

▪ Specification

Model		HA-KIT-PY2	
Door station	System parameters	Operation system	Embedded Linux operation system
		Operation mode	Single-button
		Flash	32 MB
		RAM	256 MB
Door station	Video parameters	Camera	2MP HD camera
		Resolution	Main stream: 1280*720P, 1920*1080p Sub stream: 640*480
		Night vision	Low illumination IR supplement distance: 3 m
		WDR	Support
		Field of view	Horizontal: 140° Vertical: 85°
		Video Compression Standard	H.264
Door station	Audio parameters	Audio input	Built-in 1*omnidirectional microphone
		Audio output	Built-in 1*loudspeaker, 8Ω
		Audio quality	Noise suppression and echo cancellation
		Audio compression standard	G.711 U, G.711 A
		Audio compression Rate	64 Kbps
Door station	Network parameters	Network protocol	TCP/IP, RSTP, SIP2.0
		Wired network	Support, 2-Wire wiring
Door station	Device interfaces	RS-485	/
		Alarm input	2(Exit button or door contact)
		Output	1*12 V/500 mA output
		Two-wire interface	1
		TAMPER switch	1
Door station	General	Power consumption	< 10 W
		Working temperature	-40° C to +60° C(-40° F to 140° F)

		Working humidity	10% to 95%
		Installation	Surface mounting, flush mounting
		Protection level	IP65
		Indicator	3
		Power supply	From indoor station
Indoor station	System parameters	Operation system	Embedded Linux operation system
		Memory	128 MB
		Flash	32 MB
Indoor station	Display parameters	Display screen	7-inch TFT touch screen
		Display resolution	1024 × 600
		Operation method	Capacitive touch screen
		Brightness	Adjustable
Indoor station	Audio parameters	Audio input	Built-in 1*omnidirectional microphone
		Audio output	Built-in 1*loudspeaker, 8Ω
		Audio quality	Noise suppression and echo cancellation
		Volume	Local adjustable
		Audio compression standard	G.711 U, G.711 A
Indoor station	Network parameters	Wired network	1*10 Mbps through 2-wire interface
		Wireless network	Wi-Fi 802.11 b/g/n, 2.400-2.4835 GHz
Indoor station	Device interfaces	RS-485	1
		Alarm input	8
		Two-wire (output)	1
		Two-wire (input)	1
		Power input	24VDC/1.5A
Indoor station	General	Power supply	24VDC/1.5A
		Power consumption	≤ 8 W
		Working	-10 °C to 50 °C (14 °F to 122 °F)

	temperature	
	Working humidity	10% to 90%

▪ **Available Model**

HA-KIT-PY2

▪ **Accessory**

▪ **Included**

DS-KABV8103-RS

Protective shield



Headquarters

No.555 Qianmo Road, Binjiang District,
Hangzhou 310051, China
T +86-571-8807-5998
Technical Support: support@hikvision.com

Follow us on social media to get the latest product and solution information.

