

iDS-TCS402-B/CS

Radar-Assisted Traffic Camera



- Applicable to low speed measurement scenarios, like campus, industrial park, residence, and so on.
- Integrated with millimeter wave radar and 4 MP low illumination camera.
- The real-time speed of vehicles and license plate number can be displayed on the linked screen.
- Max. 100 m speed detection distance, and max. 22 m license plate recognition distance.
- Defog, HLC, WDR, and multiple white balance modes, satisfying various scenes.
- Lane coverage: 3 lanes (ANPR & speed measurement), and speed detection range: 0-120 km/h.
- Supports license plate recognition and vehicle features recognition (vehicle type, vehicle color, no-plate vehicle capture, moving direction detection, etc).
- Free of influences from natural conditions such as illumination, visibility, bad weather, etc.





Specification

Camera		
Max. Resolution	2688 × 1520	
Min. Illumination	Color: 0.01 Lux @ (F1.2, AGC ON)	
	B/W: 0.001 Lux @ (F1.2, AGC ON)	
Shutter Time	1/25 s to 1/100,000 s	
Lens		
Focus	16 mm	
Illuminator		
External Supplement Light	Continuous LED supplement light	
Supplement Detection (Radar)		
Speed Range	0 to 120 km/h	
Max. Detectable Targets	Able to track and detect max. 128 targets	
Video		
Main Stream	50 Hz: 25 fps (2688 × 1520, 1920 × 1080, 1280 × 720, 704 × 576, 352 × 288)	
	60 Hz: 30 fps (2688 × 1520, 1920 × 1080, 1280 × 720, 704 × 576, 352 × 288)	
Sub Stragge	50 Hz: 25 fps (1920 × 1080, 1280 × 720, 704 × 576, 352 × 288)	
Sub Stream	60 Hz: 30 fps (1920 × 1080, 1280 × 720, 704 × 576, 352 × 288)	
Video Compression	H.265/H.264	
Video Bit Rate	32 Kbps to 16 Mbps	
Network		
Protocols	TCP/IP, HTTP, DNS, RTP, RTSP	
Image		
Image Settings	White Balance (Auto)	
Frame Rate	25 fps	
Day/Night Switch	ICR	
Image Enhancement	3D DNR	
Interface		
Video Output	1-ch level output	
Ethernet Interface	2, RJ45 100M/1000M self-adaptive Ethernet interface	
On-board Storage	TF card slot	
RS-485	1	
RS-232	1	
Road Traffic and Vehicle Detection	1	
Coverage	3 lanes	
	License plate recognition (LPR);	
Smart Function	Vehicle feature recognition: vehicle type classification, vehicle color recognition, no-	
	plate vehicle capture, moving direction detection	



	Mid East:
LPR Countries/Regions	Mid-East: United Arab Emirates (Abu Dhabi, Fuchaiha, Dubai, Cape Haima, Ozhman, Sharjah, Umgavan), Qatar, Iran, Iraq, Egypt, Jordan, Kuwait, Saudi Arabia, Pakistan, Oman, Lebanon, Bahrain Africa: Nigeria, Kenya, Cote d'Ivoire, South Africa, Tanzania, Mauritius, Morocco, Tunisia, Sierra Leone, Zambia, Ghana, Zimbabwe, Uganda, Angola, Ethiopia, Senegal, Algeria Asia-Pacific: Australia, New Zealand, Indonesia, Malaysia, Singapore, South Korea, Thailand, Vietnam, Philippines, Hong Kong, Macao, Taiwan, Burma, India, Mongolia, Cambodia, Laos, Bangladesh America: United States of America, Canada, Argentina, Chile, Paraguay, Uruguay, El Salvador, Bolivia, Colombia, Brazil, Ecuador, Peru, Mexico, Panama, Costa Rica, Trinidad and Tobago, Dominican, Guatemala Europe: Turkey, Croatia, Slovakia, Czech Republic, Bulgaria, Macedonia, Hungary, Greece, Poland, France, Netherlands, Switzerland, Spain, Britain, Ireland, Germany, Italy, Austria, Israel, Palestine, Belgium, Luxembourg, Albania, Kosovo Russian-Speaking Regions: Azerbaijan, Belarus, Kazakhstan, Lithuania, Georgia, Estonia, Latvia, Russian Federation, Ukraine, Moldova, Uzbekistan, Kyrgyzstan, Armenia
Accuracy (Under recommended installation and lighting conditions)	Capture rate $\geq 98\%$ Vehicle moving direction recognition accuracy $\geq 98.5\%$ LPR accuracy $\geq 98\%$ Mistaken capture rate $\leq 2\%$
Vehicle Type	Car/Van/Bus/Truck/Light Truck/SUV_MPV/Pickup/Pedestrian/Motorcycle/Tricycle
Vehicle Color	Red, yellow, green, blue, pink, purple, cyan, brown, white, grey, black Recognizable at daytime only
Vehicle Manufacturer	84 manufacturers: Hyundai, Toyota, KIA, Honda, Volkswagen, Benz, Nissan, Ford, Isuzu, BMW, Chevrolet, Mitsubishi, Renault, Opel, Suzuki, Skoda, Daewoo, Audi, Mazda, GAC HINO, Peugeot, SsangYong, Citroen, Fiat, Scania, MAN, Volvo, Lexus, Seat, Land Rover, Daihatsu, Dongwo, Subaru, Iveco, MINI, JEEP, Porsche, Chery, Dodge, Chrysler, Acura, Alfa Romeo, Great Wall, Infiniti, Smart, Saic Maxus, JAC, Jaguar, GMC, Lincoln, JMC, SAAB, FAW, Yutong, Guangzhou Yunbao, Joylong, Geely, Cadillac, JBC, An'kai, Haima, Foton, King Long, Dongfeng, Geely-Emgrand, Perodua, UD, BYD, Renault Samsung, Proton, HICOM, Malaysia_Unknown 1, Hyundai-Rohens, SsangYong-Old Version, Equus-Old Version, CNHTC, Rolls-Royce, Beiben Truck, Haval, Hino, Kia-Borrego, Chang'an, Alfa, FORO
General	
Power	24 VAC ± 10%, Max. 15 W
Dimension	226 × 206.4 × 375.3 mm (8.9 × 8.1 × 14.8 inch)
Weight	3 kg
Operating Condition	-30 °C to 70 °C (-22 °F to 158 °F); Humidity 95% or less (non-condensing)
General Function	Heartbeat, password protection, NTP time synchronization





pproval	
Safety	User name and password authentication, HTTPS digital certification
Protection	IP66
Other	Supports hardware watchdog

Available Model

iDS-TCS402-B/CS/16

Dimension





^{*}Please decide whether to use anti-corrosion devices or matched hoops and brackets according to the actual working environment.



Distributed by

HIKVISION°

Headquarters

No.555 Qianmo Road, Binjiang District, Hangzhou 310051, China T +86-571-8807-5998 overseasbusiness@hikvision.com

Hikvision USA

T+1-909-895-0400 sales.usa@hikvision.com

Hikvision Australia T +61-2-8599-4233 salesau@hikvision.com

Hikvision India T+91-22-28469900 sales@pramahikvision.com

Hikvision Canada T+1-866-200-6690 sales.canada@hikvision.com

Hikvision Thailand T +662-275-9949 sales.thailand@hikvision.com Hikvision Europe T +31-23-5542770 sales.eu@hikvision.com

Hikvision Italy T+39-0438-6902 info.it@hikvision.com

Hikvision Brazil T +55 11 3318-0050 Latam.support@hikvision.com

Hikvision Turkey T +90 [216]521 7070- 7074 sales.tr@hikvision.com

Hikvision Malaysia T+601-7652-2413 sales.my@hikvision.com Hikvision UK & Ireland T +01628-902140 sales.uk@hikvision.com

Hikvision South Africa Tel: +27 (10) 0351172 sale.africa@hikvision.com

Hikvision France T +33(0)1-85-330-450 info.fr@hikvision.com

Hikvision Kazakhstan T +7-727-9730667 nikia.panfilov@hikvision.ru

Hikvision Vietnam T +84-974270888 sales.vt@hikvision.com Hikvision UAE T +971-4-4432090 salesme@hikvision.com

Hikvision Singapore T +65-6684-4718 sg@hikvision.com

Hikvision Spain T +34-91-737-16-55 info.es@hikvision.com

Hikvision Tashkent T +99-87-1238-9438 uzb@hikvision.ru

Hikvision Hong Kong T +852-2151-1761 info.hk@hikvision.com Hikvision Russia T +7-495-669-67-99 saleru@hikvision.com

Hikvision Korea T +82-[0]31-731-8817 sales.korea@hikvision.com

Hikvision Poland T +48-22-460-01-50 info.pl@hikvision.com

Hikvision Indonesia T +62-21-2933759 Sales.Indonesia@hikvision.com

Hikvision Colombia sales.colombia@hikvision.com