

QRN-1610S

16CH 8M H.265 NVR with PoE Switch



Key Features

- Up to 16ch 8megapixel supported
- H.265, H.264, MJPEG codec supported
- 128Mbps network camera recording
- Plug & play by 16 PoE ports
- Max. 2HDDs supported
- HDMI / VGA local monitor
- P2P service (QR code connect) support

Display

Network camera	Inputs	Max. 16CH
	Resolution	8MP ~ CIF
	Protocols	Wisenet, ONVIF
Decoding	Local Display	[Clone Display] HDMI: 3840 x 2160, 1920x1080, 1280x720 VGA: 1920x1080, 1280x720
	Resolution	8MP(60fps), 5MP(90fps), 3MP(120fps), 2MP(240fps), 720p(480fps), D1(480fps)

Performance

Operating System	Embedded	Linux
Record	Compression	H.265, H.264, MJPEG
	Recording Bandwidth	Max. 128Mbps
	Resolution	8MP ~ CIF
	Mode	Normal, Schedule(Continuous/Event), Event (Pre/Post)
	Event Trigger	Alarm Input, Video Loss, Camera Event(Alarm, MD, Video Analytics, Defocus)
	Event Action	e-Mail, PTZ Preset, Alarm Out, Buzzer, Monitor Out
Search & Play	Playback Bandwidth	Max. 32Mbps(16CH simultaneously)
	User	Max. 4 Users (Local 1, Remote 3)
	Simultaneous playback	Max. 16CH(Network) Max. 8CH(Local Monitor)
	Fisheye Dewarping	N/A (processed on Web / CMS)
Storage	Supported HDD	Up to 6TB
	HDD Slot	SATA 2ea(Max. 12TB)
Backup	File backup	BU/Exe(GUI), JPG/AVI(Network)
	Function	Multi channel(Upto 8CH) Play, Date-Time/Title display

Network

Protocol	IPv4, IPv6, TCP/IP, UDP/IP, RTP (UDP), RTP (TCP), RTSP, NTP, HTTP, DHCP (Server, Client), PPPoE, SMTP, ICMP, IGMP, ARP, DNS, DDNS, uPnP, HTTPS, SNMP, ONVIF (Profile-S), SUNAPI(Server, Client)	
DDNS	Wisenet DDNS	
Transmission Bandwidth	Max. 128Mbps	
Audio	Input/Output	16 CH(network)
	Compression	G.711, G.726, AAC(16/48KHz)
	Audio Communication	2-Way
Max Remote Users	Search(3), Live Unicast(10), Multicast(20)	
Security	IP address filtering, User access Log, 802.1x, Encryption	
Web viewer	Supported OS	Windows 7, 8, 10, Mac OS X 10.9. 10.10. 10.11
	Supported browser	Plug-in free web viewer - Supported Browser: Google Chrome 47, MS Edge 20 Plug-in Webviewer - Supported MS Explore 11, Apple Safari 9 * Mac OS X only

Viewer Software		SSM, Webviewer, Smart Viewer, Wisenet mobile Support SDK/CGI(SUNAPI) for integration to 3'rd party VMS
Functions		
Camera Setup	Item	IP address, Add profile edit, Bitrate, Compression, GOP, Quality, Camera MD setup Camera video setup (Simple focus, Brightness/Contrast, Flip/Mirror, IRIS, WDR, D&N, SSNR, Shutter, SSSDR, DIS), Fisheye Dewarping Mode, Hallway View Setup, Camera Webpage
PTZ	Control	Via GUI, Webviewer, SPC-2000
Smart phone	Support Model	iOS, Android
	Protocol Support	RTP, RTSP, HTTP, CGI(SUNAPI)
	Control	Live(Multi-Profile Support), Playback
	Max. Remote Users	Search(3), Live Unicast(10)
Redundancy	ARB	Support
Easy configuration		P2P(QR code)
Interface		
HDMI		1EA
VGA		1EA
Audio		Out(1EA, RCA, Line)
Ethernet		RJ-45(10/100/1000BASE-T) x 1 RJ-45(PoE+) x 16
Alarm		In 4EA, Out 2EA
USB		2EA(Front 1, Rear 1)
Power inlet		AC 1EA
System		
System Control		Mouse, IR remocon, Web, Controller
Language		English, French, German, Italian, Spanish, Russian, Turkish, Polish, Dutch, Swedish, Czech, Portuguese, Danish, Rumanian, Serbian, Croatian, Hungarian, Greek, Norwegian, Finnish, Korean, Chinese, Japanese, Thai
Environmental		
Operating Temperature		0°C to +40°C(32°F to 104°F)
Operating Humidity		20% ~ 85% RH
Electrical		
Power Input		100~240VAC±10%
Power Consumption		Max. 158.2W(2HDDs, PoE on) Max. 34.6W(2HDDs, PoE off)
PoE Budget		Max. 100W
Mechanical		
Color / Material		Black / Metal
Dimension (WxHxD)		W370.0 x H44.0 x D320 mm (14.57" x 1.73" x 12.6") (1U)
Weight		2.79Kg (6.15lb)

- The latest product information / specification can be found at hanwha-security.com
- Design and specifications are subject to change without notice.
- Wisenet is the proprietary brand of Hanwha Techwin, formerly known as Samsung Techwin.

QRN-1610S
UNIT : mm [inch]

