

Hangzhou Huier Cable Co.,Ltd

Tel:+86-571-63792788 Fax:+86-571-63792788 Web Site: www.huiercable.com

60126: 7 CORE READER SECURITY CABLE

Construction Parameters:

Conductor:7C×14/0.20mm±0.005mm CCA

Insulation: 1.45mm ± 0.10 mm PVC

Insulation Color: Red, Blue, White, Black, Green, Yellow, Brown

Drain Wire: 7/0.19mm±0.005 TC-Tinned Copper

Shielded: Aluminum Foil

Ripcord: Yes.

Sheath: $5.8mm \pm 0.2mm$ PVC Gray

Nom. Thickness:0.65 mm

Min. Thickness: 0.60 mm

Mechanical Properties (20℃):

Rate Voltage	300V	
Rate Temperature	-15°C up to $+70$ °C	
Conductor Resistance(DC)	≤7.2Ω/100m	
Insulation Resistance(DC)	$\geq 0.010\Omega/\mathrm{km}$	
Conductor breaking elongation rate	≧15%	
Insulation tension	≥16MPa	
Sheath tension before aging	≥10MPa	
Insulation breaking elongation	≥200%	
Sheath breaking elongation before aging	≥ 125%	
Sheath breaking elongation after aging	≥100%	

Package:250M/Reel In Box

Approved:

CE, RoHS