



Hangzhou Huier Cable Co.,Ltd

Tel:+86-571-63792788

Fax:+86-571-63792788

Web Site: www.huiercable.com

60127: CORE READER SECURITY CABLE

Construction Parameters:

Conductor:7C×14/0.20mm±0.005mm CCA

Insulation:1.45mm ± 0.10mmPVC

Insulation Color: Red, Blue, White, Black, Green,Yellow,Brown

Drain Wire: 7/0.19mm±0.005 TC-Tinned Copper

Shielded: Aluminum Foil

Ripcord: Yes.

Sheath:5.8mm ± 0.2mm PVC Gray

Nom. Thickness:0.65 mm

Min. Thickness:0.60 mm



Mechanical Properties (20°C):

| | |
|---|-----------------|
| Rate Voltage | 300V |
| Rate Temperature | -15℃ up to +70℃ |
| Conductor Resistance(DC) | ≤7.2Ω/100m |
| Insulation Resistance(DC) | ≧0.010Ω/km |
| Conductor breaking elongation rate | ≧15% |
| Insulation tension | ≧16MPa |
| Sheath tension before aging | ≧10MPa |
| Insulation breaking elongation | ≧200% |
| Sheath breaking elongation before aging | ≧125% |
| Sheath breaking elongation after aging | ≧100% |

Package:100M/Plastic Reel ,4 Reels / Master Carton

Approved :

CE, RoHS