

Legrand cabling system LCS² fibre optic 19" high density fibre optic drawer



0 325 69 (not equipped)

Pack	Cat.Nos	19" high density fibre optic drawer
1	0 325 69	Modular fibre optic drawer Slide-in and modular drawer Maximum capacity: - 36 ST and SC connectors - 72 LC connectors Depth 220 mm, height 1 U Supplied with screws and wiring accessories Receives up to 3 fibre optic units below
		Fibre optic units Clip directly onto the optic drawer Cat.No 0 325 69
		Singlemode fibre units (9/125 µm)
3	0 325 73	LC duplex unit for 12 singlemode fibres - blue
3	0 325 74	LC quadriplex unit for 24 singlemode fibres - blue
3	0 325 70	ST duplex unit for 12 singlemode fibres - blue
3	0 325 71	SC duplex unit for 12 singlemode fibres - blue
3	0 325 72	MPO unit type A for 6 x 12 singlemode fibres - blue
		Multimode fibre units (62.5 and 50/125 µm)
3	0 325 78	LC duplex unit for 12 multimode fibres - beige
3	0 325 79	LC quadriplex unit for 24 multimode fibres - beige
3	0 325 75	ST duplex unit for 12 multimode fibres - beige
3	0 325 76	SC duplex unit for 12 multimode fibres - beige
3	0 325 77	MPO unit type A for 6 x 12 multimode fibres - beige
		Accessory
10	0 335 93	Blanking plate
		Accessories common to 2 fibre optic drawers
		Cassette for pigtails
1	0 329 07	12-fibre capacity
1	0 326 72	24-fibre capacity
		Bend limiting clip
10	0 335 94	Fibre management bend limiting clip

Legrand cabling system LCS² fibre optic floor distribution cabinets, equipment



0 462 91

Pack	Cat.Nos	19" fibre optic drawer equipped with SC units
1	0 335 09	Fibre optic drawer equipped with 4 SC fibre optic units for 6 multimode fibres Modular sliding drawer End stop, tilted at 45° Depth 220 mm, height 1 U Supplied with screws and wiring accessories
		OM 3 multimode optical cords (50/125 µm) Suitable for 10 Gb Ethernet network Max. optical losses: 0.3 dB For 50/125 µm multimode installations, type OM 3 Purple sheaths
		SC/SC duplex cords
3	0 326 09	Length: 1 m
3	0 326 10	Length: 2 m
3	0 326 11	Length: 3 m
		SC/LC duplex cords
3	0 326 12	Length: 1 m
3	0 326 13	Length: 2 m
3	0 326 14	Length: 3 m
		OM 3 multimode fibre optic cables (50/125 µm)
		For 50/125 µm multimode installations, type OM 3 Green sheaths Suitable for 10 Gb Ethernet network
2000	0 325 10	Tight jacketed 900 µm Internal/external (glass sheath) 6 fibres
2000	0 325 52	Internal/external (glass sheath) 24 fibres
		Fibre optic floor distribution cabinets
		Reversible metal cabinets with key-operated lock IP 20 - IK 08 Maximum capacity: - 24 fibres with ST connectors - 48 fibres with SC connectors - 96 fibres with LC connectors Up to 4 fibre optic units can be fitted Cat.Nos 0 325 71/72/73/74/76/77/78/79, 0 335 12/13/16/17/18/19 4 cable entries (2 at the top and 2 at the bottom) 12 outlets, 22 mm diameter (3 at the top, 3 at the bottom and 6 at the sides) Supplied with 1 black ISO 20 cable gland to hold the incoming cable and 15 feedthrough covers The outgoing cables can be clamped using a clamp at the back of the cabinet Can take 2 cassettes for pigtails Cat.No 0 329 07 (incoming and outgoing) 292 x 323 x 92 mm Black RAL 9005
1	0 462 91	Cabinet equipped with 2 SC fibre optic units for 12 multimode fibres
1	0 462 90	Modular cabinet