

Legrand cabling system LCS² fibre optic

optic connectors and pigtails



Pack	Cat.Nos	
1	0 326 90	Tool case for preparing optic fibres for optic connectors Provides the tools required for preparing optic cables, for carrying out initial tests of the connection of fibres to connectors and the accessories for easy connection in all situations Comprises: - Installation instructions and video - Stripping tool (for fibres and cables) - Cleaving tool - Microscope for checking the quality of the cut - Visual fault locator with cord - Accessories (ultra-strong scissors, marker, protective glasses, etc.)
1	0 326 91	Update kit for case Cat.No 0 331 93 Comprises: - Visual fault locator with cord - Adaptors for connectors - Connector support for easier connection - Fibre positioning label to be affixed to the cleaver in case Cat.No 0 331 93
		Fast-connection connectors Quick to connect, reliable and can be reused up to 5 times Microswitch for locking the fibre inside the connector and illuminated indicator for checking for faults at the end of the process These connectors do not require any glue, polishing or special tools For installation on tight jacketed fibre (diam. 900 µm) For loose jacketed fibre (diam. 250 µm), use a spreader Cat.No 0 330 48 or 0 330 49
10	0 326 57	Multimode connectors SC/UPC connector 50 µm OM3/OM4 900 µm
10	0 326 58	LC/UPC connector 50 µm OM3/OM4 900 µm
10	0 326 56	ST/UPC connector 50 µm OM3/OM4 900 µm
10	0 326 62	SC connector 62.5 µm OM1 900 µm
10	0 326 61	ST connector 62.5 µm OM1 900 µm
10	0 326 52	Singlemode connectors SC/UPC connector 9 µm OS1/OS2 900 µm
10	0 326 53	LC/UPC connector 9 µm OS1/OS2 900 µm
10	0 326 54	SC/APC connector 9 µm OS1/OS2 900 µm

Pack	Cat.Nos	
		Pigtails Supplied with 900 µm sleeve, 1 m 10 Gb - 50/125 µm OM4 LC connector Kit of 12 LC-connector pigtails 10 Gb - 50/125 µm OM3 SC connector LC connector 6 x LC-PC connectors 12 x LC-PC connectors 9/125 µm OS1/OS2 SC/APC connector SC connector LC connector 6 x LC-UPC connectors 12 x LC-UPC connectors Thermoretractable sleeve for pigtails 40 mm - pack of 50 sleeves
10	0 326 70	Glue-on connectors 50/125 and 62.5/125 µm Supplied with sleeve 900 µm Connectors with ceramic ferrule Typical attenuation: 0.3 dB ST connector SC connector LC connector
1	0 326 71	
6	0 326 22	Breakout kits For 900 µm of optical fibres Take 250 µm fibre diameters 6 fibre breakout kit 12 fibre breakout kit
6	0 326 23	
1	0 326 27	
1	0 326 26	
4	0 326 19	
6	0 326 20	
6	0 326 21	
1	0 326 25	
1	0 326 24	
1	0 327 44	
10	0 331 27	
10	0 331 47	
10	0 331 00	
1	0 330 48	
1	0 330 49	