

Legrand cabling system LCS² category 6

RJ 45 sockets - Arteor, Soliroc and Plexo









Can be integrated in all supports (p. 768 to 781)
With LCS² connector with fast connection thanks to integrated crimping take AWG 22 single-core cables up to AWG 26 and AWG multicore cables
Contacts marked with dual colour code and wiring schemes T568 A and T 568 B
Conform to standards ISO/IEC 11801 Ed. 2.0, amendment 2, EN 50173-1 and TIA/EIA 568 C

Pack		Arteor RJ 45 sockets cat. 6	Pack	Cat.Nos	Keystone RJ 45 socket cat. 6
		Mechanisms supplied with square rocker plates, to	10		UTP socket with fast connection
		be equipped with support frames (p. 384-385) and plates (p. 358-359 and 386 to 391)			Surface-mounting 1 or 2 ports box
10 10 10	5 723 02 5 728 02 5 723 54 5 728 54	Magnesium White with orange shutter Magnesium with orange shutter	20	6 327 79	For keystone connectors Provides a solution for the integration of a keystone in surface-mounting installations Can be fixed on table or in association with mini-trunking
10 10	5 723 55 5 728 55	White with green shutterMagnesium with green shutter			Soliroc RJ 45 socket cat. 6 - IK 10
10 10	5 723 14 5 728 14	UTP - 2 modules O White - square version Magnesium - square version	1	0 778 91	FTP - 2 modules IP 20 - IK 10 For at-risk areas or areas with no surveillance
5 5	5 723 53 5 728 53	Magnesium with red shutter			Plexo RJ 45 sockets cat. 6 - IP 55 closed flap IK 07 RJ 45 sockets Protection against water, dust
1 1	5 723 39 5 728 39	With integrated retractable cord (0.9 m) Winds up automatically with a pushbutton White Magnesium	5 1 1	0 695 69 0 695 61 0 695 81	For industrial sites © Grey/white FTP socket © Grey/white UTP socket Adaptor for RJ 45 socket RJ 45 to be ordered separately Weatherproofing ensured (IP 44)
10 10	5 723 22 5 728 22				plug inserted © Grey/white
10 10	5 723 16 5 728 16	FTP - 2 modules White Magnesium	1	0 904 67	Plexo 66 RJ 45 socket cat. 6 - IP 66 - IK 08 FTP socket 9 contacts Weatherproofing ensured (IP 66) with plug inserted
10 10	5 723 23 5 728 23				Inclined 90° Grey RAL 7016/T029
10 10	5 723 17 5 728 17	Shielded STP - 2 modules O White Magnesium			

