


Legrand cabling system LCS² fibre optic

19" fibre optic drawers and fibre sockets









"Tail-coat" enclosure rear for easier cable entry

0 335 09 fitted with fibre optic units

0 325 20











0 335 13

0.335.12

0 335 11 fitted with fibre optic unit 0 335 17

0.786.17

0.786.18

0 000 10		0 330 12
Pack	Cat.Nos	19" slide-in modular optic drawers
1	0 335 10	Limit switch stop with 45° slope Depth 220 mm, height 1 U Maximum capacity: - 24 x ST and SC connectors ST - 48 x LC connectors
1	0 335 09	Supplied with screws and wiring accessories Takes up to 4 fibre optic units (see below) Supplied with 24 SC connectors
		19" Linkeo optic drawers
1	0 325 20 0 325 22	adaptors)
		Fibre optic units
		Clip directly onto the fibre optic drawer Cat.No 0 335 10 or on the patch panels with fibre optic cassette Cat.No 0 335 11
1 1 1		Singlemode fibre units (9/125 µm) LC unit for 6 singlemode fibres SC unit for 6 singlemode fibres SC/APC unit for 4 singlemode fibres

Pack	Cat.Nos	Blanking plate for 19" panel
10	0 335 91	Black
1	0 320 07	Cassette for pigtails 12-fibre capacity
1	0 326 72	
		Sockets with fibre optic feedthrough
		Fitted with duplex feedthrough 2 inlets/2 outlets Used for connecting 2 fibres (fitted with their connector) Supplied with protective caps Fitted with transparent marker holder 2 modules
		Socket with fibre optic feedthrough 2 x ST Bayonet connection (STII compatible)
1	0 786 16	White
		Socket with fibre optic feedthrough 2 x SC
1	0 786 17	Push-pull connection White
		Socket with fibre optic feedthrough 2 x LC
1	0 786 18	Push-pull connection White
·	3 700 10	The state of the s
		Socket with fibre optic feedthrough 2 x SC/APC
		Push-pull connection With shutters
1	0 786 14	○ White

,	Clips directly onto the patch panels

0 335 05 Power supply via transformer provided 6 x RJ 45 ports + 1 cascade LC type optic port at

Multimode fibre units (62.5 and 50/125 μm)
0 335 16
0 335 17
0 335 18
C unit for 6 multimode fibres
C unit for 6 multimode fibres
LC unit for 6 multimode fibres

0 335 19 High-density LC unit for 12 multimode fibres

Switch/fibre optic unit

the front

For simple and fast copper to fibre conversion and vice versa Clip directly onto the patch panels
Fitted with an SC type fibre optic connector
0 335 06 10/100 base T to 10/100 base FX type SC
0 335 07 1000 base T to 1000 base SX type SC

Fibre optic cassette for patch panel Ensures fibre coiling (from 2 to 12 fibres) Takes a fibre optic unit Cat.Nos 0 335 12/13/16/17/18/19 0 335 11

Used for linking copper and fibre optic blocks on the same LCS² patch panel