

Legrand cabling system

LCS² 19" equipment



0 465 01



0 465 22



0 465 23



0 465 06



465 29



0 465 32

Technical characteristics p. 748

Pack	Cat.Nos	Fixed shelves
		For cabinets and server cabinets Quick, screw-free mounting. Black RAL 9005
		Projecting mounting on 2 x 19" uprights Height 2 U. Max. load: 15 kg
1	0 465 00	Depth 115 mm
1	0 465 01	Depth 200 mm
1	0 465 02	Depth 360 mm
		Fixing on 4 x 19" uprights Height 1 U. Max. load: 50 kg
1	0 465 05	Shelf depth 425 mm For depth 600 mm
1	0 465 06	Shelf depth 625 mm For depth 800 mm
1	0 465 07	Shelf depth 825 mm For depth 1000 mm
		Telescopic shelves For cabinets and server cabinets Quick fixing on 4 x 19" uprights Height 1 U. Max. load: 50 kg. Black RAL 9005
1	0 465 08	Shelf depth 425 mm For depth 600 mm
1	0 465 09	Shelf depth 625 mm For depth 800 mm
1	0 465 10	Shelf depth 625 mm For depth 1000 mm
		Shelves for heavy items Max. load: 100 kg For cabinets depth 1000 mm (server cabinet only for telescopic shelf) Screw fixing on 4 x 19" uprights. Black RAL 9005
1	0 465 17	Fixed shelf depth 820 mm, 1 U
1	0 465 18	Telescopic shelf depth 820 mm, 2 U
		Keyboard support shelf For cabinets and server cabinets For depth 800 mm and 1000 mm Screw fixing on 4 x 19" uprights Max. load: 50 kg. Black RAL 9005
1	0 465 19	Can take: - a computer screen - a keyboard on the retractable support - a mouse on a sliding shelf with integrated mat Area for mouse or CD
		Sets of 2 fixed sliders For cabinets and server cabinets Fixing on 4 x 19" uprights Max. load: 50 kg
1	0 465 11	For depth 600 mm
1	0 465 12	For depth 800 mm
1	0 465 13	For depth 1000 mm

Pack	Cat.Nos	19" management panels
		For organisation and circulation of patch cords Black RAL 9005
		Metal 2 axes, quick-fixing Horizontal and through run. Fitted with plastic cable guide rings radiating out for optimum protection of the cords (compliance with the bending radius) Quick, screw-free fixing
1	0 465 22 ¹	1 U
1	0 465 23 ¹	2 U
		Plastic with brushes, snap on
1	0 465 28 ²	1 U
1	0 465 29 ²	2 U
		Metal with brushes, quick-fixing Quick, screw-free fixing
1	0 465 30 ¹	1 U
1	0 465 31 ¹	2 U
		19" blanking plates Black RAL 9005
		Plastic, snap on
1	0 465 32 ²	1 U
1	0 465 33 ²	2 U
		Metal, quick-fixing Quick, screw-free fixing
1	0 465 38 ¹	1 U
1	0 465 39 ¹	2 U
1	0 465 40 ¹	3 U
		19" lighting kit 19" metal panel with a lighting kit with switch Quick, screw-free fixing Supplied with 230 V~ - 8 W fluorescent tube
1	0 464 85 ¹	1 U
		Fixing screws Set of 50 cage nuts, 50 plastic washers and 50 x M6 screws
1	0 364 53	With 8.5 mm cage nuts
1	0 364 54	With 9.5 mm cage nuts

1: Can be mounted on 19" racks with screws Cat.No 0 464 23 (see opposite)
2: Not for mounting on 19" racks