

## Legrand cabling system LCS<sup>2</sup> fibre optic

## Patch cords





Technical characteristics p. 714

Fitted with 2 connectors with ceramic ferrule at either end Packed and tested individually (report supplied) Zipcord LSZH sleeve

Pack	Cat.Nos	OS1/OS2 (UPC) singlemode optical cords
		Max. optical losses: 0.3 dB For OS1 9/125 μm singlemode installations, OS1 type Yellow sheaths
3 3 3	0 326 01	SC/SC duplex cords Length: 1 m Length: 2 m Length: 3 m
3 3 3	0 326 04	SC/LC duplex cords Length: 1 m Length: 2 m Length: 3 m
3 3 3 3 3	0 326 06 0 326 07 0 326 08	LC/LC duplex cords Length: 0.5 m Length: 1 m Length: 2 m Length: 3 m Length: 5 m
		OM 4 multimode optical cords (50/125 µm)
		Suitable for 10 Gb Ethernet network Max. optical losses: 0.3 dB For 50/125 µm multimode installations, OM 4 type Blue sheaths
3 3 3	0 326 31	SC/SC duplex cords Length: 1 m Length: 2 m Length: 3 m
3 3 3 3 3	0 326 34 0 326 35 0 326 36	LC/LC duplex cords Length: 0.5 m Length: 1 m Length: 2 m Length: 3 m Length: 5 m

Pack	Cat.Nos	OM 3 (PC) multimode optical cords (50/125 µm)
		Suitable for 10 Gb Ethernet network Max. optical losses: 0.3 dB For 50/125 µm multimode installations, OM 3 type Purple sheaths
3 3 3	0 326 09 0 326 10 0 326 11	Length: 2 m
3 3 3	0 326 12 0 326 13 0 326 14	Length: 2 m
3 3 3	0 326 15 0 326 16 0 326 17	Length: 2 m
		OM 2 (UPC) multimode optical cords (50/125 μm)
		Max. optical losses: 0.3 dB For 50/125 μm multimode installations, OM 2 type Orange sheaths
3 3 3	0 330 80 0 330 81 0 330 82	
3 3 3	0 330 69 0 330 70 0 330 71	Length: 2 m
3	0 330 72 0 330 73	3
3	0 330 61	LC/LC duplex cord Length: 2 m
3 3 3	0 330 75 0 330 63 0 330 76	Length: 2 m
3	0 330 65	LC/ST duplex cord Length: 2 m