

Remote Controls



Applications:

- Gate and Garage Door Access Control
- Panic Activation
- Arming / Disarming Alarm Systems
- Switching On / Off Security Lighting
- Machinery Control

Specifications:

Encryption Type:.....Code-Hopping
 Transmitting Range:.....100m to 400m
 Frequency - Standard:.....403.55MHz
 - Special:.....433.92MHz
 Voltage Range:.....10V to 13V DC
 Dimensions (lxbxh):.....70 x 37 x 18mm
 Gross Weight:.....31 grams
 Current Draw:.....32mA (Transmitting)
 Operating Temp:.....0°C to 49°C

Certifications:

EN300-220 Nov-1997
 SABS ETSI EN301-489-1:2001
 SABS IEC 60950:1999
 ICASA: TA-2006/759



Features:

- Utilizing secure Code-Hopping Encryption
- Unique antenna design incorporating the keyring thus increases operating range by 50%
- Crystal frequency controlled within +/- 100KHz
- Frequencies available are 403.55MHz and 433.92MHz
- 12V battery operation - GP23A Alkaline Cell
- Typically 2 years battery life expected under normal use
- LED flashes when there is a low battery condition
- Rubber buttons are easy to press and click positively
- The housing is moulded in Nylon for improved durability



PTX1
Panic Transmitter
with Pendant Chain

Order Codes:

1 Button Keyring Remote	TX1
2 Button Keyring Remote	TX2
4 Button Keyring Remote	TX4
6 Button Keyring Remote	TX6
1 Button Pendant Remote	PTX1